MATERIAL SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

1. IDENTIFICATION

PRODUCT NAME: LIQUID: 101, 102, 103, Porce-U-Glaze, Coffee, Bubble Gum, Mango, Blue

Manufacturer's Name: CALI CHEM. Inc..

Address: 14271 Corporate Dr. #B

City, State, Zip code Garden Grove, CA 92843

Business Telephone: (714) 265-3740 Emergency Telephone #:

(800)535 - 5053DATE: 04/03/2011

2. COMPOSITION / INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER:	WT/WT %
01	*Methyl Methacrylate Monome	80-62-6	70-100
02	N,N-Dimethyl-p-Toluidine	99-97-8	0.1-5
03	Ethyl Methacrylate Monomer	97-63-2	02-10
04	Trade Secret	NA	0.0-0.5

	ACGIH		OSH	A	
ITEM	TLV-TWA	TLV-STEL	PEL TWA	PEL CEILING	SKIN
01	NE	NE	NE	NE	NE
02	NE	NE	NE	NE	NE
03	NE	NE	NE	NE	NE
04	NE	NE	NE	NE	NE

^{*}Please confirm with you State Authorities to make sure that this product is legal to sell or use in your state. Cali Chem will not be liable or responsible for any products that are not legal to sell or use in your state.

3. HAZARDS IDENTIFICATION

Unstable/Reactive upon depletion of inhibitor. Check inhibitor levels periodically.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and respiratory tract and

abdominal pain.

Eyes: Eye contact may cause irritation with discomfort, tearing, or blurring of vision.

Inhalation: High concentrations irritant to the respiratory tract and may cause dizziness, headache and

anesthetic effects.

Skin: May cause skin irritation and can cause skin sensitization. Extensive/prolonged or repeated

exposure to

his material may result in a more severe skin response. Symptoms may be delayed.

4. FIRST AID MEASURES

First Aid for Eye Flush with plenty of water for 15 minutes, occasionally lifting the upper and lower

eyelids. Get medical aid. Do NOT allow victim to rub or keep eyes closed.

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15

minutes. Get medical aid if systems persist. Wash clothing before reuse.

First Aid for In case of exposure to a high concentration of vapor or mist, remove person to fresh Inhalation

air. If breathing has stopped, administer artificial respiration and seek medical

attention.

First Aid for Ingestion

Never give anything by mouth to an unconscious person. Get medial aid. Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2 to 4 cupfuls of milk

or water.

FIRE FIGHTING MEASURES

19 °C, 67°F FLASH POINT:

FLAMMABLE LIMIT AIR VOL% LOWER: 1.8

> **UPPER:** Saturation concentration.

AUTOIGNITION TEMPERATURE: 411 °C, 771 °F

EXTINGUISHER METHOD:

Chemical foam, carbon dioxide, dry chemical, water spray. FIRE AND EXPLOSION HAZARDS: High temperatures, inhibitor depletion, accidental impurities, or

exposure to radiation or oxidizers may cause spontaneous

polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.

This product is a flammable liquid. When involved in a **SPECIAL FIRE FIGHTING PROCEDURES:**

> fire, this product may ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Do not enter fire area without proper protection. Fight fire from a safe location. Heat/impurities may cause pressure to build and/or rupture closed containers, spreading fire, increasing risk of burns/injuries. Structural firefighters must wear SCBAs

and full protective equipment.

SENSITIVE TO MECHANICAL IMPACT: No. SENSITIVE TO STATIC DISCHARGE: Yes.

ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK PROCEDURES

Before cleaning any spill or leak, individuals involved must wear appropriate Personal Protective Equipment (e.g., goggles, gloves). Deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Maximize ventilation (open doors and windows) and secure all sources of ignition. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

HANDLING & STORAGE

PRECAUTIONS FOR HANDLING: Use local explosion-proof ventilation with a minimum capture

> velocity of 100 ft/min (30 m/min) at point of material release. Refer to Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental

Hygienist. Observe precautions found on label.

PRECAUTIONS FOR STORAGE:

Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. Keep container closed after each use. Ground and bond all containers when transferring. Check inhibitor levels periodically, add to the bulk material if needed. Maintain at a minimum, the original 2-inch headspace in the product container. Do not blanket or mix with oxygen-free gas as it renders the inhibitor ineffective.

INDUSTRIAL HYGIENE PRACTICES: Avoid contact with skin, eyes, clothing, and prolonged contact with the product. Use good personal hygiene and housekeeping. After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION: Refer to Section 7 regarding the ventilation requirements for

> working with this product. Use explosion-proof local exhaust at processing equipment, including buffers, sanders, grinders and polishers. High temperature processing equipment should be well

ventilated.

RESPIRATORY PROTECTION: A respirator should be worn whenever workplace conditions

> warrant a respirators use. None required if airborne concentrations are maintained below the exposure limit listed in Section 2. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate

governing standard.

EYE PROTECTION: Depending on the use of this product, splash or safety glasses may

> be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

PROTECTIVE GLOVES: If anticipated that prolonged & repeated skin contact will occur

> during use of this product, wear chemical resistant gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR

§1910.138, or other appropriate governing standards.

OTHER PROTECTIVE EQUIPMENT: No special body protection is required under typical circumstances

of use and handling. If necessary, refer to appropriate governing

standards. An eyewash station and a safety shower are

recommended.

PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE Clear, tinted liquid. **ODOR** Acrid, ester-like.

pH: ND ODOR THRESHOLD: ND

BOILING POINT: 118 °C, 246 °F

FREEZING POINT: $< -50 \square C$

VISCOSITY:

SPECIFIC GRAVITY (H₂O=1):

NE

VAPOR PRESSURE: 20 mm/Hg @ 20 °C, 68 °F

PERCENT VOLATILE W/W%: NE VAPOR DENSITY (AIR=1): 3.94 EVAPORATION RATE (BuAc =1): NE

SOLUBILITY IN WATER: 0.5% @ 20 °C, 68 °F

COEFFICIENT OF WATER/OIL DISTRIBUTION: NE

10. STABILITY & REACTIVITY

CONDITIONS TO AVOID: Temperatures above 21°C, 70°F, localized heat sources (example

drum or band heaters) oxidizing conditions, freezing conditions,

direct sunlight, ultraviolet radiation, inert gas blanketing.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong reducers, free radical

initiators, inert gases, oxygen scavengers. Material has strong

solvent properties and can soften paint and rubber.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon when burned.

HAZARDOUS POLYMERIZATION: MAY OCCUR: X WILL NOT OCCUR:

STABILITY: Unstable/Reactive upon depletion of inhibitor.

11. TOXICOLOGICAL INFORMATION

TARGET ORGANS:

For Mono Methacrylate:

For Trade Secret:

None Listed.

None Listed.

None Listed.

For N,N-Dimethyl-p-Toluidine: Liver, Central Nervous System, Blood and Skin.

TOXICITY DATA:

This product has NOT been tested on animals to obtain toxicology data. There is toxicology data for the components of the product, which is found in scientific literature. Some of this data is presented below.

For N,N-Dimethyl-p-Toluidine:

12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY:

For Monomer: There is no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. There is ecological data for the components of the product, which is found in scientific literature. Some of this data is presented below.

13. DISPOSAL CONSIDERATIONS

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

14. TRANSPORT INFORMATION

DOT/UN SHIPPING NAME: METHYL METHACRYLATE MONOMER,

STABILIZED

DOT/UN CLASS: 3

NA/UN NUMBER: UN 1247

PACKING GROUP: II

LABEL: Flammable Liquid

IMDG CLASS:

CERCLA RQ: 1000 lb.

15. REGULATORY INFORMATION

SARA Reporting Requirements: Yes

SARA Threshold Planning Quantity: There are specific Threshold Planning Quantities for the

components of this product.

TSCA Inventory Status: The components of this product are listed on the TSCA Inventory.

CERCLA Reportable Quantity (RQ): Yes

Other Federal Requirements: This product complies with the appropriate sections of the Food

and Drug Administration's 21 CFR.

Other Canadian Regulations: This product has been classified according to the hazard criteria of

the CPR and the MSDS contains all of the information required by

the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed

on the Priorities Substances List.

State Regulatory Information: This product may contain components that are covered under

specific state criteria.

RISK STATEMENTS: R11 – Highly Flammable

R36/37/38 – Irritating to eyes, respiratory system and skin.

R43 – May cause sensitization by skin contact

SAFETY STATEMENTS: S3 – Keep in a cool place.

S7 – Keep container tightly closed.

S9 – Keep container in a well ventilated place.

S16 – Keep away from sources of ignition – No Smoking.

S20 – When using do not eat or drink.

S 29 – Do not empty into drains.

16. OTHER INFORMATION

HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 2

PERSONAL PROTECTIVE EQUIPMENT: Gloves and Safety Glasses or Chemical Splash Goggles.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 2

ABBREVIATIONS:

NA Not Applicable ND Not Determined

NE Not Established

parts per million GGallon ppm Milligram mg LLiter Mole gm Gram mol kg Kilogram Micro μ Millimeter Pico mmp Pa **Pascals** cento

LCLethal ConcentrationLDLethal DoseTCToxic ConcentrationTDToxic Dose

BODBiological Oxygen DemandCODChemical Oxygen DemandLoLowestThODTheoretical Oxygen DemandTLmThreshold LimitICInhibitory Concentration

DOC Dissolved Organic Carbon

H Hours M Months
D Days Y Years

W Weeks

ABBREVIATIONS:

ACGIH American Conference of Governmental Industrial

Hygienist

CPR Controlled Product's Regulation
DSL Canadian Domestic Substances List
NDSL Canadian Non-domestic Substance List

IARC International Agency for Research for Cancer

NOEL No Observed Effect Level

NOAEL No Observed Adverse Effect Level

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit TLV Threshold Limit Value