## **MATERIAL SAFETY DATA SHEET**

Page 1 of 8

MSDS-060

Prep	ared to OSHA,	ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards	MSDS Revision: 2.0	MSDS Revision Date:	10/22/2009
		1. PRODUCT IDE	ENTIFICATION		
1.1	Product Name:				
	OPI BRUS	H CLEANER			
1.2	Chemical Name:				
	ACETONE SOL	UTION			
1.3	Synonyms:				
	NA				
1.4	Trade Names: AL 201, AL 204	ł. AL 206			
1.5	Product Use:	·			
	PROFESSIONA	L OR SUNDRY USE ONLY			
1.6	Manufacturer's Na	ame:			
	OPI PRODUCT	S, INC.			
1.7	Manufacturer's Ac				
4.5		Y STREET, NO. HOLLYWOOD, CA 91605 USA			
1.8	Emergency Phone CHEMTREC	: : +1 (703) 527-3887 / +1 (800) 424-9300			
1.9	Business Phone:				
	+1 (818) 759-2	2400 / +1 (800) 341-9999			
		2. HAZARD IDE	NTIFICATION		
2.1	Hazard Identificati				
	•	s classified as a HAZARDOUS SUBSTANCE and as DAI ad ADG Code (Australia). Flammable Liquid.	NGEROUS GOODS accordi	ng to the classification cr	iteria of NOHSC:
2.2	Routes of Entry:	Inhalation: YES	Absorption:	YES Ingestion:	YES
2.3	Effects of Exposure	H.			
	INGESTION:	If product is swallowed, may cause nausea, vomitir	ng and/or diarrhea and ce	ntral nervous system depr	ession.
	EYES & SKIN:	The liquid may produce eye discomfort and is cape			
		inflammation, ulceration. The vapor is discomforti			
		corneal burns and eye damage. Moderately irrita itching, irritation and watering. May be irritating to			
		allergic skin reactions (e.g., rashes, welts, dermatiti			auci can cause
	INHALATION:			-	piratory system.
		Symptoms of overexposure can include coughing,	wheezing, nasal congesti	on, and difficulty breathin	g. Inhalation of
		concentrated vapors can cause central nervous s		owsiness, dizziness, head	aches, nausea).
0.4	0 1 60	Odor may give some warning of exposure, but odo	r fatigue may occur.		
2.4	Symptoms of Over	·	and imitation of affected a	rama Ovaravnasura in a	
	Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or				
	repeated exp		o (o.g.,		protottiged of
2.5	Acute Health Effec	ots:			
	Moderate irrit	ation to eyes and skin near affected areas. Addition nd nausea.	ally, high concentrations o	of vapors can cause drow	siness, dizziness,
2.6	Chronic Health Eff				
	The material r	may accentuate any pre-existing dermatitis condition	n. None known		
2.7	Target Organs:				
	Eyes, skin & re	espiratory system.			
NA =	Not Available	ND = Not Determined; NE = Not Established; C = Cei	iling Limit; See Section 16 fc	or Additional Definitions of	Terms Used
NOT	E: all WHMIS re	quired information is included. It is located in approp	oriate sections based on th	ne ANSI Z400.1-2004mat.	

# $0.9 \cdot 1$

### **MATERIAL SAFETY DATA SHEET**

Page 2 of 8

MSDS-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 10/22/2009 3. COMPOSITION & INGREDIENTS EXPOSURE LIMITS IN AIR (mg/m3) **ACGIH** NOHSC OTHER ppm ppm ppm ES-ES-ES-**EINECS No.** CAS No. RTECS No. TLV **STEL** TWA PEAK STEL **IDLH** CHEMICAL NAME(S) STEL PEL 67-64-1 1800 **ACETONE** AL3150000 200-662-2 ≤ 85.0 750 1185 2375 NF 2400 1000 NE 111-90-0 **ETHOXYDIGLYCOL** KK8750000 203-919-7 ≤ 15.0 NA NA NF NF NF NA NA NA MALALEUCA ALTERNIFOLIA 68647-73-4 285-377-1 ≤ 1.0 RJ3697600 NF NF NF NA NA NA NΑ NΑ (TEA TREE) OIL 4. FIRST AID MEASURES INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. SKIN & EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove all contaminated clothing, including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately. INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention. 4.2 Medical Conditions Aggravated by Exposure: HEALTH Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, **FLAMMABILITY** 3 skin, respiratory system). REACTIVITY 0 PROTECTIVE EQUIPMENT B **SKIN EYES** 5. FIREFIGHTING MEASURES Flashpoint & Method: 17 °C (62 °F) 5.2 Autoignition Temperature: NΔ Flammability Limits: 5.3 2.5 Lower Explosive Limit (LEL): Upper Explosive Limit (UEL): 12.8 5.4 This product is an extremely flammable liquid. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO<sub>2</sub>, NO<sub>x</sub>). Extinguish all nearby sources of ignition as vapors may travel and flash back. 5.5 Extinguishing Methods Water, Foam, CO<sub>2</sub>, Dry Chemical Firefighting Procedures: 5.6 First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH-approved self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, rinse contaminated equipment with soapy water before returning to service. **HAZCHEM CODE: 2YE** 

### **MATERIAL SAFETY DATA SHEET**

Page 3 of 8

MSDS-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 10/22/2009

#### 6. ACCIDENTAL RELEASE MEASURES

6.1 Spil

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

#### 7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap & water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink, or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devices. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. Keep away from children at all times!

7.3 Special Precautions:

None.

#### 8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 Ventilation & Engineering Controls:

Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).

8.2 Respiratory Protection:

No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.

8.3 Eve Protection:

Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.

8.4 Hand Protection

None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals.

When handling large quantities (e.g., ≥ 1 gallon), wear rubber or impervious plastic gloves.

8.5 Body Protection:

No apron required when handling small quantities.

When handling large quantities (e.g.,  $\geq$  1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.

## **MATERIAL SAFETY DATA SHEET**

Page 4 of 8

Prepared to OSHA ACC, ANSI, NOHSC, WHMIS & 2001/58 FC Standards MSDS Revision: 2.0 MSDS Revision Date: 10/22/2009

Prep	pared to OSHA, ACC, ANS	I, NOHSC, WHMIS & 2001/58 EC Standards	MSDS Revision: 2.0	MSDS Revision Date: 10/22/2009
		9. PHYSICAL & CHEN	ICAL PROPERTIES	
9.1	Density:	0.80		
0.2	Boiling Point:	56 °C (133 °F)		
9.3	Melting Point:	ND		
9.4	Evaporation Rate:	< 1.0 (n-BuAc = 1.0)		
9.5	Vapor Pressure:	ND		
9.6	Molecular Weight:	NE		
9.7	Appearance & Color:	Clear liquid with a fragrant, mint-li	ke odor.	
9.8	Odor Threshold:	NE		
9.9	Solubility:	Soluble in water, alcohol and orga	unic solvents	
9.10	рН	NA		
9.11	Viscosity:	< 500 cPs		
9.12	Other Information:	NA		
		10. STABILITY &	REACTIVITY	
10.1	Stability:	TO. STABLITT &	REACTIVITI	
10.1	1 1	ambient conditions when stored properly.		
10.2	Hazardous Decomposition Produ			
	If exposed to extremely	high temperatures, products of thermal d	lecomposition may include	e irritating vapors and toxic gases (e.g
	oxides of carbon & nitro	gen).		
10.3	Hazardous Polymerization:			
	Will not occur.			
10.4	Conditions to Avoid:			
10.5	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.			
10.5	Incompatible Substances:  Strong oxidizers, peroxides, acids, alkalis or potassium t-butoxide.			
	Tollong Oxidizers, peroxic	aco, acias, antans or porassioni i botoxiac.		
		11. TOXICOLOGICA	I INFORMATION	
11.1	Toxicity Data:	TT. TOXICOLOGICA	L INI OKMATION	
11.1	This product has NOT b	peen tested on animals to obtain toxicolo d in scientific literature. These data have n		
11.2	Acute Toxicity: See Section 3.5			
11.3	Chronic Toxicity:			
	See Section 3.6			
11.4	Suspected Carcinogen:			
11.5	No  Reproductive Toxicity:			
11.5		ted to cause reproductive toxicity in huma	ns.	
	Mutagenicity:			
		ted to produce mutagenic effects in huma	ns.	
	Embryotoxicity:  This product is not report	ted to produce embryotoxic effects in hum	ane	
	Teratogenicity:	ied to produce embryotoxic effects in nom	uns.	
This product is not reported to cause teratogenic effects in humans.				
	Reproductive Toxicity: This product is not repor	ted to cause reproductive effects in human	ıs.	
11.6	Irritancy of Product: See Section 3.3			
11.7	Biological Exposure Indices: <b>NE</b>			
11.8	Physician Recommendations:  Treat symptomatically.			

### **MATERIAL SAFETY DATA SHEET**

Page 5 of 8

MSDS-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 10/22/2009 12. ECOLOGICAL INFORMATION 12.1 **Environmental Stability** The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are available, but are not presented in this MSDS. 12 2 Effects on Plants & Animals There is no specific data available for this product. 12.3 Effects on Aquatic Life: There is no specific data available for this product. Releases of large volumes may be harmful or fatal to overexposed aquatic life. Aquatic toxicity data for components of this product are available, but are not presented in this MSDS. 13. DISPOSAL CONSIDERATIONS Dispose in accordance with local, state and Federal hazardous waste laws. 13.2 Special Considerations U.S. EPA Characteristic Waste: D001 (ignitability) 14. TRANSPORTATION INFORMATION The basic description (proper shipping name, hazard class & division, ID Number, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND) CONSUMER COMMODITY, ORM-D UN1090, ACETONE SOLUTIONS, 3, II (> 1.0 L) 14 2 CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1090, ACETONE SOLUTIONS, 3, II (> 0.5 L) IMDG (OCN) 14.3 UN1090, ACETONE SOLUTIONS, 3, II, LTD QTY (≤ 1.0 L) UN1090, ACETONE SOLUTIONS, 3, II (> 1.0 L) ORM-D TDGR (Canadian GND) MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1090, ACETONE SOLUTIONS, 3, II (> 1.0 L) ADR/RID (EU): UN1090, ACETONE SOLUTIONS, 3, II, ADR, LTD QTY (≤ 1.0 L) UN1090, ACETONE SOLUTIONS, 3, II, ADR (> 1.0 L) 14.6 UN1090, SOLUCIONES DE ACETONA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L) 14.7 ADGR (AUS) UN1090, ACETONE SOLUTIONS, 3, II, LTD QTY (≤ 1.0 L) UN1090, ACETONE SOLUTIONS, 3, II (> 1.0 L)

# $0.9 \cdot 1$

### MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 10/22/2009 15. REGULATORY INFORMATION 15.1 SARA Reporting Requirements: This material contains Diethylene glycol monoethyl ether (listed as ethoxydiglycol), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373. 15.2 SARA Threshold Planning Quantity: NA 15.3 TSCA Inventory Status: All components of this product are listed in the TSCA Inventory or are exempt. 15.4 CERCLA Reportable Quantity (RQ): Acetone: 2270 kg; 5000 lbs. 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics) 15.6 This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid. State Regulatory Information: 15.7 Ingredients in this mixture on found on the following state criteria lists: California OSHA Hazardous Substances List Acetone **Delaware Air Quality Management List** Acetone Massachusetts Hazardous Substances List Acetone Minnesota Hazardous Substances List Acetone, Ethoxydiglycol **New York List of Hazardous Substances** Acetone Pennsylvania Hazardous Substances List Acetone, Ethoxydiglycol Washington Permissible Exposure Limits for Air Contaminants Acetone Wisconsin Hazardous Substances List Acetone 67/548/EEC (European Union) Requirements: 15.8 The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: Acetone: Flammable (F). R: 11-36-66-67 – Highly flammable. Irritating to eyes. Repeated exposure may

cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. S: 9-16-23-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Do not breathe

gas, fumes, vapor or spray. Take precautionary measures against static discharges.

Ethoxydiglycol: Irritating (Xi) R: 36 Irritating to eyes. S: 26 In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice.

HAZCHEM CODE: 2YE

Poison Schedule: None Allocated





## **MATERIAL SAFETY DATA SHEET**

Page 7 of 8

MSDS-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

MSDS Revision Date: 10/22/2009

Prep	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards   MSDS Revision: 2.0   MSDS Revision Date: 10/22/2009				
	16. OTHER INFORMATION				
16.1	Other Information:				
	Keep out of reach of children. Do not take internally. Store in a cool, dry place. Keep away from heat and open flame.				
16.2	Terms & Definitions:				
	Please see last page of this MSDS.				
16.3	Disclaimer:				
	This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.				
16.4	Prepared for: OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/				
16.5	Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, OR. 97759-0787 +1 (310) 370-3600 phone +1 (310) 370-5700 fax http://www.shipmate.com/				

### **MATERIAL SAFETY DATA SHEET**

Page 8 of 8

MSDS-060

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 10/22/2009

#### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists	
TLV	TLV Threshold Limit Value	
OSHA U.S. Occupational Safety and Health Administration		
PEL Permissible Exposure Limit		
IDLH Immediately Dangerous to Life and Health		

#### FIRST AID MEASURES.

71KO1 7KID 7KI	into the control of t
CPR	Cardiopulmonary resuscitation - method in which a person
	whose heart has stopped receives manual chest
	compressions and breathing to circulate blood and provide
	oxygen to the body.


### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**


0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



#### PERSONAL PROTECTION RATINGS:







#### OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

#### FLAMMABILITY LIMITS IN AIR:

Autoignition   Minimum temperature required to initiate combu		
Temperature	<b>Temperature</b> in air with no other source of ignition	
LEL		
	volume, that will explode or ignite in the presence of	
	an ignition source	
UEL	Upper Explosive Limit - highest percent of vapor in air,	
	by volume, that will explode or ignite in the presence of	
	an ignition source	

#### HAZARD RATINGS:

0 Minimal Hazard	
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
<del>-₩</del> -	Use No Water
OX	Oxidizer



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the
	exposed animals s
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the
	exposed animal
ppm	Concentration expressed in parts of material per
	million parts
TD <sub>Io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or
TC, TCo, LCio, & LCo	toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	U.S. Department of Transportation	
TC	Transport Canada	
EPA	U.S. Environmental Protection Agency	
DSL	L Canadian Domestic Substance List	
NDSL	Canadian Non-Domestic Substance List	
PSL	PSL Canadian Priority Substances List	
TSCA	TSCA U.S. Toxic Substance Control Act	
EU	EU European Union (European Union Directive 67/548/EEC)	

#### EC INFORMATION:

		M	*		<b>Q</b>	×	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful