MATERIAL SAFETY DATA SHEET

Page 1 of 8

MSDS-082G

Prep	ared to OSHA,	ACC, ANSI, NOHSC, WHMIS	S & 2001/58 EC S	Standards	MSDS Revision: 2.0	MSDS	Revision Date	:: 11/24/2008
			1. PROD	UCT IDE	NTIFICATION			
1.1	Product Name:							
	START-TO	-FINISH REGULAR F	ORMULA					
1.2	Chemical Name:							
	SOLVENT MIX	TURE						
1.3	Synonyms:							
1.4	NA Trade Names:							
1.4	NTT70, NTT65							
1.5	Product Use:							
	COSMETIC US	E ONLY						
1.6	Manufacturer's Name:							
	OPI PRODUCTS, INC.							
1.7	Manufacturer's Address: 13034 SATICOY STREET NO HOLLYWOOD CA 91405 USA							
1.8	13034 SATICOY STREET, NO. HOLLYWOOD, CA 91605 USA Emergency Phone:							
1.0	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300							
1.9	Business Phone:	. 11 (700) 327 0007 /	1 (000) 424	7000				
		2400 / +1 (800) 341-9999						
		-						
			2. HAZA	RD IDEN	NTIFICATION			
2.1	Hazard Identificat	ion:						
	•	s classified as a HAZARDOl nd ADG Code (Australia).			GEROUS GOODS acc	ording to the o	classification c	riteria of NOHSC:
2.2	Routes of Entry:		Inhalation:	YES	Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure	; ;						
	INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.							
	SKIN & EYES: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be							
	irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system.							
	INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of							
	vapors exceeding the levels listed in Section 2 (Composition and Ingredient Information) can cause central nervous							
		system depression (e.g., o	drowsiness, dizzi	iness, head	aches, nausea).			
2.4	Symptoms of Ove				as italian and imital	ion of affootod		ave a sure in avec
		skin overexposure in indiversely. Skin overexposure in indiversely.	_	iode redne	ss, nening, and iiniai	ion of directed	uleus. Overe	exposure in eyes
2.5	Acute Health Effe		_					
		rate irritation to eyes and s Idaches and nausea.	skin near affect	ed areas.	Additionally, high co	ncentrations of	vapors can c	ause drowsiness,
2.6	Chronic Health Eff	ects:						
2.7	None known. Target Organs:							
2.1		d respiratory system.						
NA =	Not Available	; ND = Not Determined; NE	= Not Establishe	ed: C = Ceil	ina Limit: See Section	16 for Addition	al Definitions o	of Terms Used
		quired information is includ			0			

MATERIAL SAFETY DATA SHEET

Page 2 of 8

MSDS-082G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

EYES

MSDS Revision Date: 11/24/2008

Propuled to GSHA, AGC, ANSI, NOTISO, WHINIS & 2001/30 EC Standards WISDS REVISION, 2.0 WISDS REVISION Butto. 11/24/2000														
		3. C	OMPOSITI	ON & INC	GREDI	ENT I	NFO	RMA	TION	1				
					EXPOSURE LIMITS IN AIR (mg/m³)									
						AC	GIH	I	NOHSC	:		OSHA		
						pp	m		ppm			ppm	ı	OTHER
CHEMICAL NAME(S) CAS No.			RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	
ALCOHOL DENATURED 64-17-5			KQ6300000	200-578-6	≤ 30.0	1000	NA				1000	NA	NA	
ETHYL	. ACETATE	141-78-6	AH5425000	201-550-6	≤ 25.0	400	NE	720	1440	NF	400	NE	2000	400 TWA
BUTYI	. ACETATE	123-86-4	AF7350000	204-658-1	≤ 20.0	150	200	730	950	NF	200	200	1700	150 TWA
HEPTANE 142-82-			MI7700000	205-563-8	≤ 10.0	400	NA				500	NA	NA	
NITRO	CELLULOSE	9004-70-0	QW0970000	NA	≤ 10.0	(10)	NE	NF	NF	NF	(10)	NE	NE	
TOSY	LAMIDE/EPOXY RESIN	130353-62-7	NA	NA	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
ISOPE	ROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	≤ 5.0	400	500	983	1230	NF	400	500	2000	400 TWA
POLY	VINYL BUTYRAL	63148-65-2	TR4955000	NA	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
TRIPH	ENYL PHOSPHATE	115-86-6	TC8400000	NA	≤ 2.0	3	NA	3	NF	NF	3	NA	NA	
	THYL PENTANYL BUTYRATE	6846-50-0	SA142000	229-937-9	≤ 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
n-BU1	YL ALCOHOL	71-36-3	EO1400000	200-001-8	≤ 2.0	50	NA	50	NF	152	100	NA	NA	
CAMPHOR		76-22-2	EX1225000	200-945-0	≤ 2.0	(2)	NA	12	19	NF	(2)	NA	NA	
METHYLENE GLYCOL (HYDRATED FORMALDEHYDE)		463-57-0	TY200000	207-339-5	≤ 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
BENZ	OPHENONE-1	131-56-6	DJ0700000	205-029-4	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 60725 81-48-1 CB7700000 201-353-5 NA			NA	NA	NA	NF	NF	NF	NA	NA	NA			
	·		4.	FIRST AIL) MEA	SURE	S							
4.1	INGESTION: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician. SKIN: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of													
	the effe	cted area with	soap and wa	•		• ,				•			_	_
		e victim to frest	n air at once.											
4.2	Medical Conditions Aggravat None known.	ea by Exposure:						H	EALI	H				1
								F	LAM	MAB	ILITY			3
								R	EAC	TIVIT	Υ			0
								Р	ROTE	CTIV	/E EQ	UIPA	ΛENT	Α
1	PROTECTIVE EQUIPMENT A													

$0.\mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 3 of 8

MSDS-082G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 11/24/2008

5. FIREFIGHTING MEASURES

Flashpoint & Method: 5.1

> -4 °C (24 °F) estimated. Autoignition Temperature:

NA

5.2

5.3

Flammability Limits:

Lower Explosive Limit (LEL):

Upper Explosive Limit (UEL):

NE

5.4 Fire & Explosion Hazards

WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.

5.5 Extinguishing Methods


HazChem Code: 3YE

Hazard Identification Number: 33 CO₂, Halon, Dry Chemical, Foam

5.6 Firefighting Procedures

> This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.

> First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



6. ACCIDENTAL RELEASE MEASURES

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

Work & Hygiene Practices:

Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

7.2 Storage & Handling

> Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).

Special Precautions:

Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

Incompatible Substances: **None known.**

MATERIAL SAFETY DATA SHEET

Page 4 of 8

MSDS-082G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 11/24/2008 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Ventilation & Engineering Controls: 8.1 When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8.2 Respiratory Protection No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.3 Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166. 8.4 If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.5 **Body Protection** No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Density: 0.9980 - 1.0008 Boiling Point: NA 9.3 Melting Point ΝE 9.4 Evaporation Rate: NΑ 9.5 Vapor Pressure: NA Molecular Weight 9.6 9.7 Appearance & Color: Viscous liquid with ester-like (fruity) odor 9.8 Odor Threshold: ND Solubility: 99 Insoluble in water NA 9.11 Viscosity 1000 cPs to 3000 cPs 9 12 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stable under ambient conditions when stored properly (see Section 7, Storage and Handling) 10.2 Hazardous Decomposition Products If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO₂). 10.3 Hazardous Polymerization May occur, if exposed to extremely high temperatures. This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide).

MATERIAL SAFETY DATA SHEET

Page 5 of 8

MSDS-082G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 11/24/2008 11. TOXICOLOGICAL INFORMATION Toxicity Data: 11.1 This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity See Section 2.5 11.3 Chronic Toxicity: See Section 2.6 11 4 Suspected Carcinogen This product contains Isopropyl Alcohol, which is not carcinogenic to humans, but is listed as a Group 3 carcinogen by the IARC. Reproductive Toxicity 11.5 This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans. Irritancy of Product: See Section 2.3 11.7 Biological Exposure Indices: NF 11.8 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: K_{OC} = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: K_{OC} = 1.82. Water solubility: 120 parts H₂O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log Kow = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. Effects on Plants & Animals: 12.2 There are no specific data available for this product. There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-082G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 11/24/2008

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1263, PAINT, 3, II (> 0.5 L)
14.3	IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.5	ADR/RID (EU): UN1263, PAINT, 3, II, ADR, LTD QTY (≤ 1.0 L)
14.6	MEXICO (SCT): UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)
14.7	ADGR (AUS): UN1263, PAINT, 3, 3 °(b), LTD QTY (≤ 1.0 L)



15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

SARA 304 (40 CFR Table 302.4) – Butyl Acetate, Ethyl Acetate, Isopropyl Alcohol

15.2 SARA Threshold Planning Quantity:

There are no specific Threshold Planning Quantities for the components of this product.

15.3 TSCA Inventory Status

The components of this product are listed on the TSCA Inventory.

15.4 CERCLA Reportable Quantity (RQ):

Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

15.6 Other Canadian Regulations:

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.



15.7 State Regulatory Information:

Ingredients in this mixture on found on the following state criteria lists:

ingredients in this thixtore on toolid on the following state effection usis.

Delaware Air Quality Management List Massachusetts Hazardous Substances List

California OSHA Hazardous Substances List

Michigan Critical Substances List Minnesota Hazardous Substances List

New Jersey Right to Know Hazardous Substances List

New York List of Hazardous Substances Pennsylvania Hazardous Substances List

Washington Permissible Exposure Limits for Air Contaminants Wisconsin Hazardous Substances List

Butyl Acetate, Ethyl Acetate, Isopropanol, Diacetone Alcohol,

Propyl Acetate

Butyl Acetate, Ethyl Acetate, Nitrocellulose, Butyl Acetate, Ethyl Acetate, Isopropanol

Nitrocellulose, Camphor

Diacetone Alcohol, Propyl Acetate Butyl Acetate, Ethyl Acetate, Isopropanol

Camphor, Diacetone Alcohol, Propyl Acetate

Isopropanol, Nitrocellulose, Diacetone Alcohol, Propyl Acetate

Butyl Acetate, Ethyl Acetate,

Butyl Acetate, Ethyl Acetate, isopropanol, Nitrocellulose

Camphor

Butyl Acetate, Ethyl Acetate, Isopropanol, Triphenyl Phosphate

Ethyl Acetate, Diacetone Alcohol, Propyl Acetate

 $\mathbf{D} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 7 of 8

MSDS-082G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 11/24/2008

15. REGULATORY INFORMATION - continued

67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC:

Ethyl Acetate: Flammable (F). R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.

Butyl Acetate: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.



16. OTHER INFORMATION

Other Information: 16.1

> EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. KEEP OUT OF REACH OF CHILDREN.

16.2 Terms & Definitions:

Please see last page of this MSDS.

16.3 Disclaimer

> This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

Prepared for:

OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/

 $0.6 \cdot 1$

16.5 Prepared by:

ShipMate, Inc.

18436 Hawthorne Boulevard, Suite 201 Torrance, CA 90504

+1 (310) 360-3700 phone

+1 (310) 360-5700 fax

http://www.shipmate.com/

Dangerous Goods Training & Consulting

MATERIAL SAFETY DATA SHEET

Page 8 of 8

MSDS-082G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

MSDS Revision Date: 11/24/2008

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDs. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number
--

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL Permissible Exposure Limit	
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiop	oulmona	ry resi	uscitation -	method in	which a	person
	whose	heart	has	stopped	receives	manual	chest
	compressions and breathing to circulate blood and provide						
	oxygen	to the b	ody.				


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:







Vapor Respirator







Dust & Vapor

Respirator





Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion
Temperature	in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by
	volume, that will explode or ignite in the presence of
	an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air,
	by volume, that will explode or ignite in the presence of
	an ignition source

HAZARD RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	
-W-	Use No Water	
OX	Oxidizer	



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o Or TC, TC _o , LC _{Io} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)

EC INFORMATION:

The state of the s		M	*		9	X	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful